

# MGM 101 / 1982

## 2 V Madenci Baş Lamba Kablosu

2 V Miner's Helmet Lamp Cable



### YAPI

- 1 İletken**  
Elektrolitik ince, çok telli  
bükülü kalaylı bakır tel,  
Sınıf 5
- 2 İzolasyon**  
Doğal kauçuk
- 3 Dış Kılıf**  
Yağ, mazota ve alev  
dayanıklı kloropren kauçuk

### CONSTRUCTION

- Conductor**  
*Fine multi-wire stranded tinned  
electrolytic copper wire,  
Class 5*
- Insulation**  
*Natural rubber*
- Outer Sheath**  
*Chloroprene rubber resistant  
to oil, fuel and flame*

Standart MGM 101/1982

Standard MGM 101/1982



## MGM 101 / 1982

## 2 V Madenci Baş Lamba Kablosu / 2 V Miner's Helmet Lamp Cable

Kesit (mm <sup>2</sup> ) Cross-Section	1	1.5	2.5	4	6	10	16	25	35	50	70	95	120	150	185	240	300	
Max. DC Direnç (Ω/km) Max. DC Resistance	18.1	12.1	7.4	4.61	3.08	1.83	1.15	0.727	0.524	0.387	0.268	0.193	0.154	0.126	0.100	0.0762	0.0601	
Nominal Ağırlık (kg/km) / Nominal Çap (mm) / Nominal Weight (kg/km) / Nominal Diameter (mm)																		
1																		
2	90/9																	
3																		
4																		
5																		
7																		
10																		
12																		
14																		
16																		
19																		
24																		
27																		
33																		
37																		

Damar Sayısı / Number of Cores